AW01 Mono Color Flexible LED Wall Grazer

(No Dimming Function)

AW01 is designed to provide high quality illumination for columns and curved architectonic surfaces, with a variety of lens options that can be used for flood lighting, wall grazing, wall washing and accent lighting. Equipped with 18 pcs rotatable and waterproof high-power module, it is flexible in horizontal way. With 12VDC input, one constant voltage power supply can load 2 meters in continuous length without brightness degradation from start to end.

Dimension

L66*W39*H29mm



Bending



Min. Bending Diameter



Product Features

I. Flexible structure with continuous illumination without any shadows or dark areas.

II. DC12V Input, extend or combine length freely.

III. Multiple lens options.

IV. IP67, suitable for wet locations and has a protection rating of IK06.

Product Application

Application areas: wall grazing, cove light, wall wash, residential, hospitality, restaurants, museums.

Cover Styles

A
Standard

B
Honeycomb



C
Shading

Ansi C78.377

SDCM<3

One Bin

Rating

5 Years Warranty

Ambient Temp.

Class 3

CE

IK06

Technical Parameters

Electrical	
Input Voltage	12V DC
Power Consumption	36W/m

Physical	
LED Count	18 LEDs/m
Min. Unit	3 pcs LEDs/ unit
Min. Unit Length	166 mm
Housing Material	Aluminum +Tempered Glass Cover

Output	
LED Light	SMD LED 3535
CRI	>80, >90
Max. Single Feed Length	2M
Optional Lens	15°, 20°, 30°, 40°, 10°x15°, 15°x25°
	15°x40°
Lumen Maintenance	70,000 Hours L70 @ 25°C
	50,000 Hours L70 @ 50°C

Temperature Ranges	
Installation	0°C to 50°C
Operating	-25°C to 50°C

Dependability	
Warranty	5 Years Warranty
IP Rating	IP67

Optional Color	
	2200K(2238±102K)
	2700K(2725±145K)
	3000K(3045±175K)
	3500K(3465±245K)
	4000K(3985±275K)
	4500K(4503±243K)
	5000K(5029±283K)
	6500K(6532±510K)
	Green(520-530nm)
	Blue (455-465nm)

Lighting OLYMPIA

E-mail: info@olympialed.com
Https: //www.olympialed.com

AW01 Mono Color Flexible LED Wall Grazer

Optional LENS Distribution

Model Encoding

AW01 - 12V - 3535 -18 - 3000K- 80 -1525 - A

Product No.

Input Voltage

LED Type

LED Quantity/Meter

CCT & Color

2200K, 2700K, 3000K, 3500K, 4000K, 4500K, 5000K, 6500K

G=Green, B=Blue

Color Rendering Index

80=Ra>80, 90=Ra>90

Lens Distribution

15=15° 20=20° 30=30° 40=40°

1015=10°×15° 1525=15°×25° 1540=15°×40°

Cover Styles

A=Standard B=Honeycomb C=Shading

Mounting Optionals

Fixed Bracket





WJJ-CYJ-035

Adjustable Bracket











AW01-ACC-HX-S2830C2

Lighting OLYMPIA

E-mail: info@olympialed.com
Https: //www.olympialed.com

AW01 Mono Color Flexible LED Wall Grazer

Available Custom Length

Min. L=166mm(3×LED) 3 Links (6W)





Length =333mm(6×LED) 6 Links (12W)



Length =666mm(12×LED) 12 Links (24W)



L=1000mm(18×LED) 18 Links (36W)

L=1333mm(24×LED) 24 Links (48W)



Maximum Linking 2×L=2000mm(L=1000mm)



Lighting OLYMPIA
E-mail: info@olympialed.com
Https: //www.olympialed.com

AW01 Mono Color Flexible LED Wall Grazer

Shading Accessories Dimension







Connection