



# F08 Mono Color LED Linear Flex

F08-24V-2835-120-2200K-6500K

## Specification





## Technical Parameters


Electrical	
Input Voltage	24V DC
Power Consumption	10W/m
Physical	
LED Count	120 LEDs/m
Cutting Unit	12 LEDs
Cutting Unit Length	100 mm
Minimum Bend Diameter	150mm
Output	
LED Light	Epistar SMD LED 2835
CRI	>80, >90
Max Run Length*	
Single Feed	5M
Double Feed	10M
Beam Angle	120°
Lumen Maintenance	70,000 Hours L70 @ 25°C 50,000 Hours L70 @ 50°C
Temperature Ranges	
Installation	0°C to 50°C
Operating	-25°C to 50°C
Dependability	
Warranty	3 Years Warranty
IP Rating	IP68 Wet location submersible <2m

Optional Color	Lumen Output
	2200K(2238±102K) 440lm/m
	2700K(2725±145K) 454lm/m
	3000K(3045±175K) 500lm/m
	3500K(3465±245K) 510lm/m
	4000K(3985±275K) 522lm/m
	4500K(4503±243K) 515lm/m
	5000K(5209±283K) 505lm/m
	6500K(6532±510K) 498lm/m
	Green(520-530nm) 532lm/m
	Blue (455-465nm) 76lm/m
	Red (620-630nm) 160lm/m

## Illuminance Distribution



## White Color Charts



# F08 Mono Color LED Linear Flex

## Connection

