


F18 SPI Pixel Chasing RGBW LED Linear Flex

F18-24V-5050-70-SPI4-RGBW

Specification



Dimension

Vertical Bending

Min. Bending Diameter

Beam Angle

Pixel RGBW

SPI

Dimmable

Submersible

Ambient Temp.

Class 3

LM-80

IK08

UV resistant

Flame Resistant

Saltwater Resistant

Solvents Resistant

Dirt Resistant

CE

RoHS

Warranty


Technical Parameters

Electrical	
Input Voltage	24V DC
Power Consumption	18W/m
Physical	
LED Count	70 LEDs/m
Cutting Unit	7 LEDs
Cutting Unit Length	100mm
Minimum Bend Diameter	120mm
Output	
LED Light	Epistar SMD LED 5050
Color	RGBW(2700K/3000K/4000K/5000K)
Working Mode	SPI
Pixels Quantity	10 Pixels/m
IC Chips	UCS8904
Max Run Length*	
Single Feed	8M
Double Feed	16 M
Beam Angle	210°
Lumen Maintenance	70,000 Hours L70 @ 25°C 50,000 Hours L70 @ 50°C

Emitting Color	Lumen Output
	Red 86lm/m
	Green 254lm/m
	Blue 50lm/m
	RGBW 591lm/m
	3000K 270lm/m

Temperature Ranges	
Installation	0°C to 50°C
Operating	-25°C to 50°C
Dependability	
Warranty	3 Years Warranty
IP Rating	IP68 Wet location submersible <2m

Illuminance Distribution



F18 SPI Pixel Chasing RGBW LED Linear Flex

