SP05 Mono Color Silicone LED Strip Light

SP05-48V-2835-84-CC-2200K~6500K

Specification





Technical Parameters

Electrical	
Input Voltage	48V DC (Built-in Constant Current)
Power Consumption	5W/m
Physical	
LED Count	84 LEDs/m
Cutting Unit	14 LEDs
Cutting Unit Length	166.7 mm
Minimum Bend Diameter	50mm
Output	
LED Light	Epistar SMD LED 2835
CRI	>80, >90
Max Run Length*	
Single Feed	50 M
Double Feed	100 M
Beam Angle	210°
Lumen Maintenance	70,000 Hours L70 @ 25°C 50,000 Hours L70 @ 50°C
Temperature Ranges	
Installation	0°C to 50°C
Operating	-40°C to 55°C
Dependability	
Warranty	5 Years Warranty
IP Rating	IP67

Optional Color

- 2200K(2238±102K)
- 2500K(2460±120K)
- 2700K(2725±145K)
- 3000K(3045±175K)
- 3500K(3465±245K)
- 4000K(3985±275K)
- 4500K(4503±243K)
- 5000K(5209±283K)
- 5700K(5667±355K)
- 6500K(6532±510K)
- Green(520-530nm)
- Blue (455-465nm)
- Lemon Yellow (570-580nm)
- Pink (610-620nm)

Illuminance Distribution







Lighting OLYMPIA

Email: info@olympialed.com
Http://www.olympialed.com

SP05 Mono Color Silicone LED Strip Light

Connection



Email: info@olympialed.com
Http://www.olympialed.com

SP05 Configuration and Accessories

Mold injection Connector (IP67 Factory Assembly Only)



Direct Entry Connector
MJ-SP05-A-D01/02/03
MJ-SP05-A-D01SM
MJ-SP05-A-D02SF
MJ-SP05-A-D03SFM





End Cap





Jumper
MJ-SP05-A-D-JC



DIY Connector (IP65 Rating Protection)



DIY Front Connector plug
DIY-S-FR-SP05-D





DIY End Cap plug
DIY-S-END-SP05

SP05 Configuration and Accessories

DIY Connective Cable
S-2C-18AWG-D6-UL-06



Double Coated Tissue Tape
3M-4229
3m/rolls
Width:12mm



Waterproof Interrupter



Male Connector
M12-M-2C-18AWG-D6-W-0327-S





Female Connector
M12-F-2C-18AWG-D6-W-0327-S



SP05 Configuration and Accessories



Middle Power Connector (1 to 2)
MID-CNR-A-1T2





Middle Power Connector (2 to 2)
MID-CNR-A-2T2





Male Connector End Cap
SYZ-EC-M12-M





Female Connector End Cap
SYZ-EC-M12-F-2C



Plastic Mounting Channel



Dimension



Unit:mm

Installation Way



Surface Mounted





Model	W x H(mm)	Standard Length	Screw Holes	Holes Numbers	Suitable Product
PCSP05S01-02	14.41*8.20	20mm	Φ3.0mm	1	SP05
PCSP05S01-100		1000mm	Φ3.0mm	2	SP05

Product Packing Details

Standard : Carton (White Carton+Paper Reel Inside)

Product	Max.length/Reel	Carton Size	Net Weight	Gross Weight
F15/SF15	30m	35*35*19cm	12.0kg	13.6kg
F16/SF16	28m	35*35*19cm	12.9kg	14.5kg
SF17	28m	35*35*19cm	12.9kg	14.5kg
SF18	28m	35*35*19cm	12.9kg	14.5kg
F21/SF21	20m	35*35*19cm	10.4kg	12.0kg
SF10	35m	35*35*19cm	11.2kg	12.8kg
SF09	45m	35*35*19cm	7.7kg	9.3kg
SF08	60m	35*35*19cm	14.4kg	16.0kg
SF06	60m	35*35*19cm	14.4kg	16.0kg

Standard : Carton (White Carton+ Roll up packing Inside)

Product	Coiling Max. length	Quantity (Roll)	Carton Size	Net Weight	Gross Weight
SP01	10m	10	35*35*19cm	20.0kg	21.6kg
SP05	11m	10	35*35*19cm	19.8kg	21.4kg
SF05	11m	10	35*35*19cm	18.0kg	19.6kg
SF06	8m	14	35*35*19cm	26.8kg	28.4kg
SF08	8m	14	35*35*19cm	26.8kg	28.4kg
SF09	8m	10	35*35*19cm	14.4kg	16.0kg
SF10	6m	11	35*35*19cm	21.2kg	22.8kg
F15/SF15	6m	7	35*35*19cm	16.8kg	18.4kg
F16/SF16	4.5m	9	35*35*19cm	18.7kg	20.3kg
SF17	4.5m	9	35*35*19cm	18.7kg	20.3kg
SF18	4.5m	9	35*35*19cm	18.7kg	20.3kg
F21/SF21	4.5m	9	35*35*19cm	21.0kg	22.6kg
SF24	13m	2	41*41*19cm	15.6kg	17.5kg

Email: info@olympialed.com
Http://www.olympialed.com

Product Packing Details

Custom : Carton (White Box+Plastic Plate Inside)

Product	Packing 1				Packing 2			
	Packing 1 Max. Length	Quantity (Plate)	Carton Size	Gross Weight	Packing 2 Max. Length	Quantity (Plate)	Carton Size	Gross Weight
F15/SF15	5m	1	41*41*5cm	2.5kg	10m	1	57*48*6cm	5.0kg
		4	41*41*19cm	10.6kg		5	57*48*19cm	25.0kg
F16/SF16	5m	1	41*41*5cm	2.5kg	10m	1	63*53*6cm	5.0kg
		4	41*41*19cm	10.0kg		3	63*53*16cm	15.0kg
SF17	5m	1	41*41*5cm	2.5kg	10m	1	63*53*6cm	5.0kg
		4	41*41*19cm	10.6kg		3	63*53*16cm	15.0kg
SF18	5m	1	41*41*5cm	2.5kg	10m	1	63*53*6cm	5.0kg
		4	41*41*19cm	10.6kg		3	63*53*16cm	15.0kg
F21/SF21	5m	1	41*41*5cm	3.1kg	10m	1	63*53*6cm	6.2kg
		4	41*41*19cm	13.0kg		3	63*53*16cm	18.6kg
SP01	10m	1	41*41*5cm	2.6kg	20m	1	57*48*6cm	5.0kg
		4	41*41*19cm	11.0kg		5	57*48*19cm	25.0kg
SP05	10m	1	41*41*5cm	2.4kg	20m	1	57*48*6cm	3.6kg
		4	41*41*19cm	9.6kg		5	57*48*19cm	18.0kg
SF05	10m	1	41*41*5cm	2.0kg	20m	1	57*48*6cm	4.0kg
		4	41*41*19cm	8.0kg		5	57*48*19cm	20.0kg
SF06	7m	1	41*41*5cm	2.3kg	14m	1	57*48*6cm	4.4kg
		4	41*41*19cm	9.2kg		5	57*48*19cm	22.0kg
SF08	7m	1	41*41*5cm	2.3kg	14m	1	57*48*6cm	4.4kg
		4	41*41*19cm	9.2kg		5	57*48*19cm	22.0kg
SF09	9m	1	41*41*5cm	2.0kg	18m	1	57*48*6cm	3.9kg
		4	41*41*19cm	8.0kg		5	57*48*19cm	19.5kg
SF10	5m	1	41*41*5cm	2.3kg	10m	1	57*48*6cm	4.2kg
		4	41*41*19cm	9.2kg		5	57*48*19cm	21.0kg
SF24	5m	1	57*48*6cm	2.3kg	10m	1	63*53*6cm	4.2kg
		4	57*48*19cm	9.2kg		5	63*53*16cm	21.0kg
SF33	3m	1	63*53*6cm	3.4kg	10m	1	85*73*6cm	11.5kg
		3	63*53*16cm	10.2kg		2	85*73*11cm	23.0kg
SF34	3m	1	63*53*6cm	3.2kg	10m	1	85*73*6cm	11.0kg
		3	63*53*16cm	9.6kg		2	85*73*11cm	22.0kg